FEATURES

* HIGH SPEED
* HIGH POWER
* AVAILABLE FOR PULSE OPERATING
* CLEAR TRANSPARENT COLOR PACKAGE

PACKAGE DIMENSIONS



NOTES:
1. All dimensions are in millimeters (inches).
2. Tolerance is ±0.25mm(.010") unless otherwise noted.
3. Protruded resin under flange is 1.5mm(.059") max.
4. Lead spacing is measured where the leads emerge from the package.
5. Specifications are subject to change without notice.

ABSOLUTE MAXIMUM RATINGS AT T_A=25℃

PARAMETER	MAXIMUM RATING	UNIT
Power Dissipation	120	mW
Peak Forward Current (300pps, 10 μs pulse)	1	A
Continuous Forward Current	100	mA
Reverse Voltage	5	V
Operating Temperature Range	-40℃ to + 85℃	
Storage Temperature Range	-40℃ to + 85℃	
Lead Soldering Temperature [1.6mm(.063") From Body]	260℃ for 6 Seconds	

ELECTRICAL / OPTICAL CHARACTERISTICS AT T_A=25℃

PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT	TEST CONDITION
Radiant Intensity	I_E	20	36	-	mW/sr	I_F = 20mA
Peak Emission Wavelength	λ_P	-	865	-	nm	I_F = 20mA
Spectral Line Half-Width	$\Delta\lambda$	-	25	-	nm	I_F = 20mA
Forward Voltage	V_F	-	1.45	1.65	V	I_F = 20mA
Forward Voltage	ΔV_F	-	-	0.4	V	V_F@ 50mA-V_F@ 20mA
Reverse Current	I_R	-	-	10	μA	V_R = 5V
Reverse Voltage	V_R	5	-	-	V	I_R = 100 μA
Viewing Angle (See FIG.6)	$2\theta_{1/2}$	25	30	-	deg.	I_F = 20mA
Dice Center	-	0	-	0.12	mm	-

TYPICAL ELECTRICAL / OPTICAL CHARACTERISTICS CURVES

(25℃ Ambient Temperature Unless Otherwise Noted)



FIG.1 SPECTRAL DISTRIBUTION



FIG.2 FORWARD CURRENT VS. AMBIENT TEMPERATURE



FIG.3 FORWARD CURRENT VS. FORWARD VOLTAGE



FIG.4 RELATIVE RADIANT INTENSITY VS. AMBIENT TEMPERATURE



FIG.5 RELATIVE RADIANT INTENSITY VS. FORWARD CURRENT



FIG.6 RADIATION DIAGRAM