FEATURES

∗RECTANGULAR LIGHT BAR.
∗LARGE, BRIGHT, UNIFORM LIGHT EMITTING AREAS.
∗LOW POWER REQUIREMENT.
∗HIGH BRIGHTNESS & HIGH CONTRAST.
∗SOLID STATE RELIABILITY.
∗CATEGORIZED FOR LUMINOUS INTENSITY.

DESCRIPTION

The LTL-2620M-01 is a light bar rectangular light sources designed for a variety of applications where a large bright source of light is required. This device utilizes is multi-color applicable LED chips. The green LED chips, which are made from GaP on a transparent GaP substrate. The red orange & yellow LED chips, which are made from GaAsP on a transparent GaP, and has white bar.

DEVICE

PART NO.	DESCRIPTION
MULTI-COLOR	Universal
LTL-2620M-01	Rectangular Bar

PACKAGE DIMENSIONS



NOTES: All dimensions are in millimeters. Tolerances are± 0.25 mm (0.01“) unless otherwise noted.

INTERNAL CIRCUIT DIAGRAM



THE SIGN " " IS STANDARD FOR RED ORANGE CHIP.
THE SIGN " " IS STANDARD FOR YELLOW CHIP.
THE SIGN " " IS STANDARD FOR GREEN CHIP.

PIN CONNECTION

No	CONNECTION
1	CATHODE A
2	ANODE A
3	ANODE B
4	CATHODE B
5	CATHODE C
6	ANODE C
7	ANODE D
8	CATHODE D
9	CATHODE E
10	ANODE E
11	ANODE F
12	CATHODE F
13	CATHODE G
14	ANODE G
15	ANODE H
16	CATHODE H

ABSOLUTE MAXIMUM RATING AT Ta=25°C

PARAMETER	RED ORANGE	YELLOW	GREEN	UNIT
Power Dissipation Per Segment	75	60	75	mW
Peak Forward Current Per Segment (1/10 Duty Cycle, 0.1ms Pulse Width)	100	80	100	mA
Continuous Forward Current Per Segment Derating Linear From 25℃ Per Segment	25 0.33	20 0.27	25 0.33	mA mA/℃
Reverse Voltage Per Segment	5	5	5	V
Operating Temperature Range	-35℃ to +85℃			
Storage Temperature Range	-35℃ to +85℃			
Solder Temperature: max 260℃ for max 3sec at 1.6mm below seating plane.				

ELECTRICAL / OPTICAL CHARACTERISTICS AT Ta=25°C

RED ORANGE

PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT	TEST CONDITION
Average Luminous Intensity	I_V	800	2000		μcd	I_F=10mA
Peak Emission Wavelength	λp		630		nm	I_F=20mA
Spectral Line Half-Width	Δλ		40		nm	I_F=20mA
Dominant Wavelength	λd		621		nm	I_F=20mA
Forward Voltage Per Segment	V_F		2	2.6	V	I_F=20mA
Reverse Current Per Segment	I_R			100	μA	V_R=5V
Luminous Intensity Matching Ratio	I_V-m			2:1		I_F=10mA

YELLOW

PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT	TEST CONDITION
Average Luminous Intensity	I_V	800	2000		μcd	I_F=10mA
Peak Emission Wavelength	λp		585		nm	I_F=20mA
Spectral Line Half-Width	Δλ		35		nm	I_F=20mA
Dominant Wavelength	λd		588		nm	I_F=20mA
Forward Voltage Per Segment	V_F		2.1	2.6	V	I_F=20mA
Reverse Current Per Segment	I_R			100	μA	V_R=5V
Luminous Intensity Matching Ratio	I_V-m			2:1		I_F=10mA

GREEN

PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT	TEST CONDITION
Average Luminous Intensity	I_V	800	2000		μcd	I_F=10mA
Peak Emission Wavelength	λp		565		nm	I_F=20mA
Spectral Line Half-Width	Δλ		30		nm	I_F=20mA
Dominant Wavelength	λd		569		nm	I_F=20mA
Forward Voltage Per Segment	V_F		2.1	2.6	V	I_F=20mA
Reverse Current Per Segment	I_R			100	μA	V_R=5V
Luminous Intensity Matching Ratio	I_V-m			2:1		I_F=10mA

Note: Luminous intensity is measured with a light sensor and filter combination that approximates the CIE (Commision Internationale De L'Eclairage) eye-response curve.

TYPICAL ELECTRICAL / OPTICAL CHARACTERISTIC CURVES

(25°C Ambient Temperature Unless Otherwise Noted)



Fig1. RELATIVE INTENSITY VS. WAVELENGTH



Fig2. FORWARD CURRENT VS. FORWARD VOLTAGE



Fig3. RELATIVE LUMINOUS INTENSITY VS. FORWARD CURRENT



Fig4. RELATIVE LUMINOUS EFFICIENCY (LUMINOUS INTENSITY PER UNIT CURRENT) VS. PEAK CURRENT



Fig5. FORWARD CURRENT VS. FORWARD VOLTAGE



Fig6. RELATIVE LUMINOUS INTENSITY VS. FORWARD CURRENT



Fig7. RELATIVE LUMINOUS EFFICIENCY (LUMINOUS INTENSITY PER UNIT CURRENT) VS. PEAK CURRENT



Fig8. MAX. ALLOWABLE DC CURRENT VS. AMBIENT TEMPERATURE.



Fig9. MAX. PEAK CURRENT VS. DUTY CYCLE % (REFRESH RATE 1KHz)



Fig10. MAX. PEAK CURRENT VS. DUTY CYCLE % (REFRESH RATE 1KHz)

NOTE: YG=GREEN E=RED ORANGE Y=YELLOW